



TOTAL QTY.	PIPE SIZE	MODEL	A	B	C	D	E	F	G	MAX. MOVE.	WT. (Lbs.)
		23	3-1/4"	5-1/2"	5-7/8"	4-1/4"	5/8"	1-3/4"	3"	4"	6
		24	3-3/4	6-1/2	7	4-1/2	5/8	1-3/4	3	4	8
		25	4-1/8	7-3/8	8	5-1/4	5/8	1-3/4	3	4	9
		26	5	9-1/4	10-3/8	6-1/4	5/8	1-3/4	3	4	12
		27	6	11-3/8	12-1/2	7-1/4	5/8	2-3/4	4	6	22
		28	7	13-3/8	14-1/2	8-1/4	5/8	2-3/4	4	6	36
		29	8	15	15-3/4	10	3/4	4	6	8	45
		30	9	17	17-3/4	11	3/4	4	6	8	52
		31	9-3/4	18-3/4	20-1/8	12	3/4	4	6	8	95
		32	11-1/8	21-1/8	22-1/8	13-1/2	7/8	4	6	8	110
		33	12-1/8	23-1/8	24-1/8	14-1/2	7/8	6	8	8	125
		34	13	25	26-5/8	15-1/2	7/8	6	8	8	155
		35	14-3/4	27-3/4	28-5/8	17-1/2	1-1/8	6	8	12	240
		36	16-1/2	31-1/2	32-5/8	19-1/2	1-1/8	6	8	12	295

**NOTES:**

- #1 - MODEL 29 TO 36 (4) BOLTS — MODEL 23 TO 28 (2) BOLTS
- #2 - MATERIAL: CARBON STEEL      FINISH: ONE COAT OF PAINT

SEE PAGE 2 FOR MODEL SELECTION GUIDE.

CUSTOMER \_\_\_\_\_

PROJECT \_\_\_\_\_

ENGINEER \_\_\_\_\_

CONTRACTOR \_\_\_\_\_

P.O. NO \_\_\_\_\_

**CONNECTALL** LYÉE LTD

Tél. : (514) 335-7755 Fax : (514) 335-6573

DESCRIPTION: **SPIDER 10 PIPE GUIDE**

DRAWN BY: \_\_\_\_\_ DATE: \_\_\_\_\_ DRAWING NO: **SPIDER 10**

P.B. \_\_\_\_\_

## MODEL SELECTION CHART — SPIDER GUIDES

PIPE SIZE	INSULATION THICKNESS						
	1"	1½"	2"	2½"	3"	3½"	4"
½"	23	23	24	25	26	26	27
¾"	23	24	25	26	26	27	27
1"	23	24	25	26	26	27	27
1¼"	23	24	25	26	26	27	27
1½"	24	24	25	26	26	27	27
2"	24	25	26	26	27	27	28
2½"	25	25	26	26	27	27	28
3"	25	26	26	27	27	28	28
4"	26	26	27	27	28	28	29
5"	27	27	27	28	28	29	30
6"	27	27	28	28	29	30	30
8"	28	28	29	30	30	31	31
10"	30	30	30	31	31	32	32
12"	31	31	31	32	32	33	33
14"	32	32	32	32	33	33	34
16"	33	33	33	33	34	34	35
18"	34	34	34	34	35	35	36
20"	35	35	35	35	36	36	36
24"	36	36	36	36	—	—	—

When ordering Spider Guides, specify insulation thickness.  
 Spider available for Copper Tubing. Contact factory for pricing.